

with reference to OSHA Hazard Communication Standard (HCS) published in Federal Register 77 FR 17574 – March 2012

Flame Retardant Volara

All Colors, All Densities

Volara Flame Retardant Grades:

AF, AFL, AFM, AFR, AFX, AGF, ASF EOF, LMF, MF, VSF, LFO, MRL, SF, EAF

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

Product Name: Volara

Synonyms: Crosslinked Polyolefin Foam

Use of the Product: Applications requiring low flammability

Manufacturer: Sekisui Voltek, LLC

100 Shepard Street Lawrence, MA 01843

Emergency Information: Sekisui Voltek, LLC

100 Shepard Street Lawrence, MA 01843

(M-F: 8-5 EST) (Weekends/Evenings)

978-685-2557 978-685-6186

SECTION 2: HAZARD(S) IDENTIFICATION

Hazard Designation: None

Additional Information: Molten polymer will cause thermal burns to skin. When heated irritating

fumes may be produced.

Inhalation of fumes and vapors generated by heating foam may cause soreness or irritation in the nose and throat. Exposure to dust may

Status: 04/05/2018

cause irritation.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Description: Expanded, closed cell physically crosslinked foam consisting of

Polyolefins and Colorants.

SECTION 4: FIRST AID MEASURES

In Case of Eye Contact: Flush particles from eyes with clean flowing water or eye wash solution

for several minutes. Seek medical attention if discomfort persists.

In Case of Skin Contact: If heated material contacts the skin, immediately quench with cool

flowing water. If foam/polymer sticks to skin, do not peel, seek

MSDS No: 0700 04/05/2018 Page 1 of 5



with reference to OSHA Hazard Communication Standard (HCS) published in Federal Register 77 FR 17574 – March 2012

immediate medical attention. If the burn is severe, obtain immediate

Status: 04/05/2018

emergency medical attention.

In Case of Ingestion: If ingested, seek medical attention.

In Case of Inhalation: If symptoms are experienced, move affected individuals to fresh air.

Obtain medical attention if breathing difficulty persists.

SECTION 5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media: SMALL FIRE: Use dry chemical, CO2, water spray

LARGE FIRES: Water Spray

Hazardous Combustion

Products: Include hydrogen bromide, hydrogen cyanide, oxides of nitrogen,

carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.

Protective Equipment/

Clothing: Wear an approved positive pressure self-contained breathing apparatus

and firefighter turnout gear.

INSTRUCTIONS: Use flooding quantities of water until well after fire is extinguished.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: See Section 8, EXPOSURE CONTROLS/PERSONAL PROTECTION

Environmental Precautions: Pick up and retain for recycle or disposal.

Methods for Cleaning Up: Pick up mechanically.

SECTION 7: HANDLING AND STORAGE

Safe Handling: Keep scrap material off walking surfaces as this can create slipping

hazards. Avoid accumulation of dust in enclosed space. Use in well-ventilated area. Use good housekeeping practices during storage,

transfer, and handling.

Safe Storage: Recommend storage indoors with adequate fire sprinkler protection.

Store away from excessive heat, ignition sources and oxidizing agents. Keep poly-bag container closed to prevent moisture exposure, soiling and contamination. Foam rolls can be heavy, stacking rolls is not

recommended.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

General Health Controls: Ventilate storage and use areas to prevent accumulation of dust and

fumes.

Personal Protection:

Eye Protection: Safety glasses are recommended.

MSDS No: 0700 04/05/2018 Page 2 of 5



with reference to OSHA Hazard Communication Standard (HCS) published in Federal Register 77 FR 17574 – March 2012

Skin Protection: Not normally considered a skin hazard under anticipated conditions of

normal use.

To protect against contact with molten product use suitable protection,

Status: 04/05/2018

gloves and clothing.

Respiratory Protection Use appropriate respiratory protection.

Hand Protection: Gloves are recommended for further processing like sawing, cutting or

thermoforming.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Solid

Color: According to product color.

Odor: Faint, mild hydrocarbon odor.

Melting Point: 104 - 138 °C (219 - 280 °F)

Boiling Point: Not applicable

Flash Point: Not applicable.

pH: Not applicable

Vapor Pressure: Not applicable

Viscosity: Not applicable

Specific Gravity: 0.02 to 0.40 (water = 1)

Water Solubility: Insoluble

Evaporation Rate: Not applicable

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: The product is stable.

Conditions to Avoid: Avoid sparks, open flame or excessive heat. Avoid contact with oxidizers.

Incompatibility with: Material may be softened by some hydrocarbons. Reacts with fluorine gas.

SECTION 11: TOXICOLOGICAL INFORMATION

Product

Summary: Volara is not considered to be toxic to humans or animals.

ACUTE ORAL

EFFECTS: None Known.

SKIN EFFECTS: None Known.

MSDS No: 0700 04/05/2018 Page 3 of 5



with reference to OSHA Hazard Communication Standard (HCS) published in Federal Register 77 FR 17574 – March 2012

Reproductive /

Development Effects None known.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Ecotoxicity is expected to be minimal based on the low water solubility of

Status: 04/05/2018

polymers.

Environmental Fate: Unknown.

Bioaccumulation: Unknown.

SECTION 13: DISPOSAL CONSIDERATIONS

Use only licensed transporters and permitted facilities for waste disposal. Recycle whenever possible.

SECTION 14: TRANSPORT INFORMATION

Proper Shipping

Name: Crosslinked Polyolefin Foam

DOT Hazard Class: Not Regulated

UN/NA ID: Not Regulated Marine Pollutant: Unknown

Packing Group: Not applicable NAER Guidebook: Not Regulated

Labels: Not Regulated DOT Status: Not Regulated

SECTION 15: REGULATORY INFORMATION

California Proposition 65

This product contains contain substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: OTHER INFORMATION

DISCLAIMER OF RESPONSIBILITY:

The data in this safety data sheet describes the safety requirements of our product based on our current level of knowledge and may not be considered to guarantee any product properties and it is sufficient for United Nations' Globally Classification and Labeling of Chemicals (GHS) standard Harmonized System of Classification and Labeling of Chemicals (GHS) standard

However, the information is provided without any warranty, expressed or implied, regarding it's correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any

MSDS No: 0700 04/05/2018 Page 4 of 5



Safety Data Sheet with reference to OSHA Hazard Communication Standard (HCS) published in Federal Register 77 FR 17574 – March 2012

way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Status: 04/05/2018

MSDS No: 0700 04/05/2018 Page 5 of 5